## Technical Specification - GreaseShield®1000-PF





### **APPLICATIONS**

- Prep Sinks
- Small Pot Wash Sinks

#### FLOW RATES & CERTIFICATION

- Pro-Active Flow Rate 1 L/sec
- ASME Certification
- PDI Certification
- CSA Certication
- EN 1825 Certification

#### STANDARD FEATURES & FUNCTIONS

- Automatic FOG & solids removal
- Self cleaning
- Magnetic baffle for bioremediation
- PLC controlled
- Non restricted Vortex Flow Control device
- Reverse flow configuration
- Space Saver Running Trap & Sampling Point
- Globally certified award winning technology
- The only Green Certified grease trap in the world



PRO-ACTIVE

1L/s

FLOW RATE

PRE-FILTER

FOR SOLID WASTE SEPARATION

Inlet 1"½/40mm Outlet 2"/50mm Hot Water Solenoid ¾"/22m

Electrical RatingsUSAUK,EU,AU,NZVoltage120v230vFrequency60Hz50HzCurrent0.98A0.49A

#### **Standard Operational Times**

Days of Operation 7 Days a Week Hours of Operation 07:00-02:30

Note: Operational times should be adjusted to suit the needs of the kitchen

**Average Power Consumption**15.1W Per Hour

#### **CERTIFICATIONS & APPROVALS**

- Global GreenTag LCA Rate Gold Certification
- PDI G101 (Plumbing & Drainage Institute)
- ASME A112.14.3 & A112.14.4 (American Society of Mechanical Engineers)
- NSF International (National Sanitation Foundation)
- CSA (Canadian Standards Association) Grease Interceptors
- UL (Underwriters Laboratory)
- IAPMO (International Association of Plumbing and Mechanical Officials) Uniform Plumbing Code Certification Mark
- CE Conformity with Health, Safety and Environmental Protection \ Standards with the European Economic Area (EEA)
- EN1825 (European Standard for Grease Separators)
- KIWA (ETA DK, Swedac & SINTEF) Sweden, Norway and Finland.
   European Institution for Testing, Inspection and Certification

V4 05/06/2019

# Technical Specification - **GreaseShield®1000-PF**

